



HEAVY DUTY MOTOR OIL (15W-40 CI-4)

DESCRIPTION:

PEAK® PERFORMANCE SAE 15W-40 CI-4 HEAVY DUTY MOTOR OIL provides outstanding protection in both on-road and off-road applications and in both diesel and gasoline engines, including diesel engines incorporating Exhaust Gas Recirculation (EGR). PEAK® PERFORMANCE SAE 15W-40 CI-4 HEAVY DUTY MOTOR OIL is designed to withstand shear down, viscosity loss and thickening from heavy soot loading and oxidation, even when operating under extreme conditions.

BENEFITS:

- Meets API Service Classification CI-4
- Meets Cummins CES 20078
- Meets Detroit Diesel Power Guard 93K214
- Meets Caterpillar ECF-1
- Recommended for both diesel and gasoline engines, reducing inventory
- Helps control oil thickening and provides outstanding filterability with the newer highsoot producing emission controlled engines
- Protects against varnish, sludge and carbon deposits
- Meets API Service Classification CH-4, CF-2, CF, CE, CD-II for use in older engines

APPLICATION:

PEAK® PERFORMANCE SAE 15W-40 CI-4 HEAVY DUTY MOTOR OIL is recommended for use in all naturally aspirated, turbo charged or super turbo charged diesel, gasoline and propane engines in on-road and off-road applications. PEAK® PERFORMANCE SAE SAE 15W-40 CI-4 HEAVY DUTY MOTOR OIL is designed for use in the latest turbo charged, low emission engines featuring EGR technology.

Viscosity recommendations vary according to temperature and engine manufacturer. Always consult your owner's manual for correct viscosity choice and API Service Category recommendations.



HEAVY DUTY MOTOR OIL
15W-40 CI-4

Official Motor Oil
of the



Official Motor Oil
of the



HEAVY DUTY MOTOR OIL (15W-40 CI-4)

PRODUCT PART NUMBERS:

Test (Method)	15W-40	Drum Part Number	P4M051
API Gravity (ASTM D-1298)	29.045	SAE Viscosity Grade	15W-40
Viscosity		API Classification	SM
'@ 40 °C, cSt (ASTM D-445)	113.27	ILSAC	CI-4
'@ 100 °C, cSt (ASTM D-445)	15.07		
Viscosity Index (ASTM D-2270)	138	Bulk Part Number	P4M050
Noack Volatillity (D-5800)	N/A	SAE Viscosity Grade	15W-40
Sulfated Ash, wt% (D-874)	1.3	API Classification	SM
TBN	10.3	ILSAC	CI-4

15W-40

Drum UPC Code	0-74804-03444-8
Case UPC Code	N/A
Case SCC-14 Code	N/A

Heavy Duty Shipping Information

Unit	Pack	Unit Weight Pallet	Weight Units	Units per Pallet	Pieces per Truck	Pallets per Truck
Drums	55 Gallon	450 lbs.	1,800 lbs.	4 drums	84 drums	21
Bulk	Gallon	7.3 lbs.	N/A	N/A	N/A	6,500

HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at www.peaklubricants.com, or by calling Old World Industries' PEAK technical support line at 1-800-477-5847.



Distributed by
Old World Industries, Inc.
Northbrook, IL 60062
p 800.323.5440
w peaklubricants.com

PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, Inc. IndyCar® Series (and Design) and Indianapolis 500 (and Design) are trademarks of Brickyard Trademarks, Inc., used with permission.

PM032610