



## HEAVY DUTY MOTOR OIL (30 SN)

### DESCRIPTION:

---

PEAK® PERFORMANCE HEAVY DUTY SAE 30 MOTOR OIL is formulated with an advanced additive technology and premium base oils to protect engines under all service conditions. The low sulfated ash formula is designed to provide excellent performance in two stroke diesel engines calling for a product meeting API CF-2 service classification.

### BENEFITS:

---

- Exceeds API CF-2/SN Service Classification
- High detergency formula is designed to help keep engines clean and soot suspended in the oil
- Outstanding dispersancy and oxidation resistance helps protect engines against excessive viscosity and the subsequent deposit formation and wear that can result
- Eliminates the need for extra oil additives
- Helps prevent engine wear and extend engine life
- Helps reduce internal engine friction

### APPLICATION:

---

PEAK® PERFORMANCE HEAVY DUTY SAE 30 MOTOR OIL is recommended for use in on-road and off-road diesel applications, as well as heavy duty gasoline fleets, operating under all service conditions.

**Viscosity recommendations vary according to temperature and engine manufacturer. Always consult your owner's manual for correct viscosity choice and API Service Category recommendations.**



Official Motor Oil  
of the



Official Motor Oil  
of the



## HEAVY DUTY MOTOR OIL (30 SN)

### PRODUCT PART NUMBERS:

<b>Test (Method)</b>	<b>30</b>	<b>Quart Part Number</b>	<b>P3M007-02</b>
API Gravity (ASTM D-1298)	27.4	SAE Viscosity Grade	30
Flash Point, °C (D-287)	220	API Classification	SN
Pour Point, °C (D-5950/D97)	-18		
Viscosity		<b>Drum Part Number</b>	<b>P3M001-01</b>
'@ 40 °C, cSt (ASTM D-445)	98.84	SAE Viscosity Grade	30
'@ 100 °C, cSt (ASTM D-445)	11.42	API Classification	SN
Viscosity Index (ASTM D-2270)	100		
Noack Volatillity (D-5800)	N/A		
Sulfated Ash, wt% (D-874)	1.2		

### 30

Quart UPC Code	0-74804-01508-9
Case UPC Code	0-74804-11508-6
Case SCC-14 Code	6-00-74804-01508-1

### Heavy Duty Shipping Information

Unit	Pack	Unit Weight Pallet	Weight Units	Units per Pallet	Pieces per Truck	Pallets per Truck
Quart	12/1 Quarts	2.2 lbs.	1129 lbs.	528 quarts	15,840 qts.	30
Drum	55 Gallon	450 lbs.	1800	4 Drums	84 Drums	21

**HANDLING AND SAFETY INFORMATION** Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at [www.peaklubricants.com](http://www.peaklubricants.com), or by calling Old World Industries' PEAK technical support line at 1-800-477-5847.



Distributed by  
Old World Industries, LLC  
Northbrook, IL 60062  
p 800.323.5440  
w [peaklubricants.com](http://peaklubricants.com)  
©2011

PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, LLC. IndyCar® Series (and Design) and Indianapolis 500 (and Design) are trademarks of Brickyard Trademarks, Inc., used with permission.