



AUTOMATIC TRANSMISSION FLUID (DEXRON® - VI)

DESCRIPTION:

PEAK® Professional Dexron® – VI Automatic Transmission Fluid is a specially formulated synthetic fluid designed to meet the requirements of GM's DEXRON - VI specification. PEAK Performance DEXRON - VI Automatic Transmission Fluid is formulated to provide extended service life over that of a DEXRON®-III (H) ATF and offers exceptional performance in both new and older transmissions.

BENEFITS:

- Outstanding friction properties that provides smooth gear shifting in low temperature conditions
- Extended fluid life
- Resistant against sludge and deposit formation
- Improved oxidation and thermal stability
- Protects against wear
- Good foam resistance
- Backwards compatible for use in older GM automatic transmissions

APPLICATION:

PEAK® Professional Dexron® – VI Automatic Transmission Fluid is recommended for use in passenger car and light truck automatic transmissions that require a General Motors DEXRON®-VI or earlier generation DEXRON® fluid. It is also recommended for use in new GM 6-speed automatic transmissions, and is fully backwards compatible with older GM automatic transmissions. PEAK Performance DEXRON® - VI Automatic Transmission Fluid may be used in various industrial and mobile hydraulic systems operating over a wide temperature range.





DEXRON® - VI
AUTOMATIC TRANSMISSION FLUID

Official Motor Oil
of the



Official Motor Oil
of the



AUTOMATIC TRANSMISSION FLUID (DEXRON® - VI)

PRODUCT PART NUMBERS:

Quart Part Number PDT067
SAE Viscosity Grade ATF
API Classification Dexron® - VI
ILSAC N/A

Drum Part Number PDT061
SAE Viscosity Grade ATF
API Classification Dexron® - VI
ILSAC N/A

Test (Method) ATF
API Gravity (ASTM D-287) Viscosity 35.76
'@ 40 °C, cSt (ASTM D-445) 29.5
'@ 100 °C, cSt (ASTM D-445) 5.83
Viscosity Index (ASTM D-2270) 145

ATF
Quart UPC Code 0-74804-03372-4
Case UPC Code 0-74804-13372-1
Case SCC-14 Code 1-00-74804-03372-1

PRODUCT SHIPPING INFORMATION:

Pack/Units Per Case	12/1 Quart	Pallets/Cases Per Truck	21/1,764
Cubic Feet	.73 cu Ft.	Units Per Truck	21,168
Case Dimensions	13.25" L x 10.25" W x 9.25" H	Pallet Size	48" L x 40" W x 60.5" H
Cases Per Pallet	84	Cases/Rows High	14/6

HANDLING AND SAFETY INFORMATION Refer to Old World Industries Material Safety Data Sheet (MSDS). The MSDS is available from your PEAK Performance Supplier at www.peaklubricants.com, or by calling Old World Industries' PEAK technical support line at 1-800-477-5847.



Distributed by
Old World Industries, Inc.
Northbrook, IL 60062
p 800.323.5440
w peaklubricants.com

PEAK and the PEAK Mountain Graphic are Registered Trademarks of Old World Industries, Inc. IndyCar® Series (and Design) and Indianapolis 500 (and Design) are trademarks of Brickyard Trademarks, Inc., used with permission.